



N49 PRIMER

POROUS SUBSTRATE PRIMER FOR POLYURETHANE SEALANT SYSTEMS

24 November 2017

YOUR SMART ADVANTAGES

- Clear appearance
- Promotes high bond strength of polyurethane sealants on porous substrates
- One part – no mixing required

DESCRIPTION

Bostik N49 Primer is a primer designed for use with the Bostik polyurethane sealant range to ensure adhesion to porous substrates, particularly with water immersed applications. Bostik polyurethane sealants requiring the application of Bostik N49 Primer on porous substrates only are:

- Bostik Seal 'N' Flex® 1
- Bostik Seal 'N' Flex® FC
- Bostik Construction PU
- Bostik Fireban® One

USES

Bostik N49 Primer can be used on porous substrates:

Concrete
Render
Brick
Blockwork
Lightweight blocks
Unglazed ceramic tiles

PRODUCT CHARACTERISTICS

Colour	Clear
Appearance	Thin, colourless liquid
Coverage	1 litre: Approx. 50 lineal metres of joint per litre
Drying time	15 minutes
Composition	Moisture sensitive
Product codes	
1 L can	30608602
4 L can	30608477

SURFACE PREPARATION

Prior to applying Bostik N49 Primer the substrate must be sound, dry, clean and free from any dust, residue or contamination and meet the requirements of substrate preparation detailed in the applicable Polyurethane Sealant Technical Data Sheet.

Bostik primers or sealants must not be applied to unpredictable absorptive surfaces such as marble, limestone or granite unless a standard of appearance has been agreed on a result of testing for stain and/or discoloration.

APPLICATION

Bostik N49 Porous Substrate Primer

- **Bostik N49** is clear in appearance, and formulated for use on porous substrates such as concrete, render & and masonry.
- **Bostik N49** is not suitable for application on non-porous substrates such as hard plastics and ferrous or non-ferrous metals. Refer Bostik N40 Primer Technical Data Sheet for non-porous substrate applications.
- Apply with a soft brush allowing a minimum drying time of 15 minutes before applying sealant.
- **Bostik N49** is moisture sensitive and will commence curing when exposed to ambient moisture. To maximize adhesion results:
 1. Decant the required qty that can be applied by brush within 30 minutes into a clean, dry container.
 2. Primer that changes colour or becomes thicker has commenced to cure and should be discarded.
 3. Avoid dipping the same brush into the original container unless the entire contents are applied in 30 minutes.
 4. Use a clean, dry container on each decant to avoid contamination and shortened pot life.
 5. Discard any unused primer; do not pour any unused primer back into any remaining original primer in the original container.

Sealant must be applied within 4 hours or re-priming is required. A sample test application is recommended on all substrates as staining may occur where the primer has been applied to areas not covered by polyurethane sealant.

BOSTIK N49 PRIMER

APPLICATION Cont.

Primer Yield Guide

1 litre of primer will coat approximately 50 lineal metre of concrete joint interface, depending on wastage and substrate type.

BOSTIK CO-OPERATIVE TEST PROGRAM

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

Important Note

The information given in this guide is based on Bostik experience and is correct to the best of our knowledge.

However, since the use of our products in accordance with the instructions given, and their success in application are dependent on a number of factors, we can only be responsible for the quality of our products at the time of dispatch.

Should any doubt arise about specification or application, our Technical Service Department should be contacted immediately.

As the information given herein is of a general nature, we cannot assume any responsibility.

Success will always depend on the peculiarities of the individual case. We also refer to our standard conditions of sale.

PRIMER SELECTION TABLE

This Primer Selection guide for Polyurethane Sealants is provided to assist the user with the appropriate primer, which will ensure the optimum level of adhesion for the sealant to the substrates, noted.

SUBSTRATE	SEAL 'N' FLEX 1	SEAL 'N' FLEX FC	CONST. PU	FIREBAN ONE
Concrete	N49	N49	N49	N49
Masonry Brick	N49	N49	N49	N49
Masonry Blockwork	N49	N49	N49	N49
Lightweight Blocks	N49	N49	N49	N/A
Plasterboard	NPR	NPR	NPR	NPR
Ceramic Tiles - unglazed	N49	N49	N49	N/A
ABS Rigid Plastic	N40	N40	N40	N/A
uPVC Rigid Plastic	N40	N40	N40	N40
Brass, Bronze	N40	N40	N40	N40
Copper	N40	N40	N40	N40
Aluminium Mill Finish	N40	N40	N40	N/A
Aluminium Anodized	N40	N40	N40	N/A
Bright Steel	N40	N40	N40	N/A
Galvanised Steel	N40	N40	N40	N/A
Stainless Steel	N40	N40	N40	N/A
Porcelain	N40	N40	N40	N/A
Ceramic Tiles - Glazed	N40	N40	N40	N/A
Fibreglass Gel Coated	N40	N40	N40	N/A

Recommendations given have been obtained from laboratory tests and can be considered as guiding values. Every substrate will vary from surface to surface and testing is advisable before applying primers or sealants. Please consult our technical services department for further information.

Key:

Bostik N49	Porous Substrate Primer
Bostik N40	Non Porous Substrate Primer
NPR	No Primer Required
N/A	Not Applicable

REFER TO SPECIFIC TECHNICAL DATA SHEET ON INDIVIDUAL SEALANT FOR ADDITIONAL INFORMATION ON INSTALLATION AND APPLICATION.

BOSTIK N49 PRIMER

STORAGE AND SHELF LIFE

Store between 5°C and 30°C. Shelf life is twelve months in original unopened container

SAFETY PRECAUTIONS

SEE THE MATERIAL SAFETY DATA SHEET FOR ADDITIONAL INFORMATION.
EMERGENCY INFORMATION: 1800 033 111 (ALL HOURS)
MSDS can be downloaded from www.bostik.com.au

CLEAN UP

Clean up uncured material and equipment immediately after use using **Bostik 9907** solvent. Do not use solvents on skin. Cured Bostik Polyurethane Primer is difficult to remove via chemical means and mechanical means may be necessary.

PRECAUTIONS IN USE

Complete details on each of the products mentioned are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that all concerned read the appropriate Safety Data Sheets. Visit www.bostik.com/au for copies.

For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.

BOSTIK HOTLINE
Smart help 1800 898 551



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com/au