



## Aquaproof Dual Mastic

Polymer Enhanced Bentonite Paste

### Features

- ▶ Bentonite Paste
- ▶ 400% Expansion
- ▶ Green Concrete
- ▶ Detailing Paste
- ▶ Below Grade

241 Ingles Street  
Port Melbourne, VIC 3207  
Ph: (03) 9429 9111

4/14 Tennyson Road  
Gladesville, NSW 2111  
Ph: (02) 9817 4441

[www.pasco.net.au](http://www.pasco.net.au)

### Product Description

**Aquaproof Dual Mastic** is a polymer enhanced bentonite paste used to detail pipe penetrations, inside corners, concrete voids and tieback cover details. The expandable characteristics of **Aquaproof Dual Mastic** can exceed 400% if unrestricted.

### Basic Uses

**Aquaproof Dual Mastic** is an important detail of the **Aquaproof Dual** waterproofing systems. See specific waterproofing system detailed drawings for application techniques.

### Installation

For complete installation guidelines, please contact your Pasco Sales Representative.

Apply with a trowel or a rubber glove. Fill concrete voids with **Aquaproof Dual Mastic** until flush with surface. For detailing of lagging tie-backs, apply a coating of **Aquaproof Dual Mastic** to the tie-back nut and to any voids. Fill the **Aquaproof Dual** tie-back covers with **Aquaproof Dual Mastic**. Install the cover over the tie-back bolt and secure the nails. For vertical/horizontal transitions and other inside corners, apply 50mm fillet of **Aquaproof Dual Mastic** to the inside corner and cover with **Aquaproof Dual** waterproofing membrane.

### Storage

Store on skid or pallet, cover with polyethylene or tarp. Do not store above 45°C.

### Limitations

Protected **Aquaproof Dual Mastic** from moisture prior to installation of the **Aquaproof Dual** waterproofing system. Please contact Pasco for compatibility testing or if conditions of salt or contaminants exist.

### Typical Physical Properties

Physical Property	Test Method	Value
Colour		Black/Grey
Odour		Mild
Sodium Bentonite		62% by weight
Unrestricted Expansion		400%
Absorption		200%
Installation Temperatures	ASTM D746	-30°C to 40°C

Pasco Construction Solutions Pty Ltd offers its' products for sale, subject to its standard terms and conditions of sale, which are available upon request. All endeavors have been made to ensure the information provided in this technical data sheet is accurate and correct, however as the use of this material is beyond the supplier's control, liability is limited to replacement of material proven faulty. It is the responsibility of the purchaser to ensure that the product is suitable for the specific application and that it is applied in accordance with the supplier's recommendations.