



Aquaproof Dual Seam Tape

Polyethylene Film

Features

- ▶ Seam Tape
- ▶ Excellent Adhesion
- ▶ 72mm Width
- ▶ Easy to Apply
- ▶ Below Ground
- ▶ Backfill Protection
- ▶ Eliminates Open Laps

241 Ingles Street
Port Melbourne, VIC 3207
Ph: (03) 9429 9111

4/14 Tennyson Road
Gladesville, NSW 2111
Ph: (02) 9817 4441

www.pasco.net.au

Product Description

Aquaproof Dual Seam Tape is a polyethylene film supporting a polyester/cotton cloth carrier with a natural rubber adhesive. **Aquaproof Dual Seam Tape** provides aggressive adhesion to the joint, when used in conjunction with **Aquaproof Dual** waterproofing membranes, **Aquaproof Dual Seam Tape** unifies the layer of HDPE waterproofing and protects the seams during backfilling.

Basic Uses

Aquaproof Dual Seam Tape is used for covering and protecting the seams in **Aquaproof Dual** waterproofing membranes.

Installation

Examine all surfaces prior to starting application. Dust and debris must be removed. The seam should be clean and dry. Apply **Aquaproof Dual Seam Tape** over the seam with 40mm overlap on each sheet. Cover the nail holes when possible. Apply direct pressure to the **Aquaproof Dual Seam Tape** using a solid hand roller.

Storage

Protect from moisture. Store on skid or pallet, cover with polyethylene or tarp.

Packaging

Roll size: 72mm x 55m, 16 rolls per carton.

Limitations

Aquaproof Dual Seam Tape does not provide a gasproof barrier. Use **Aquaproof Dual Bitumen Tape** for greater vapor and water barrier protection.

Typical Physical Properties

Physical Property	Test Method	Value
Materials		Polyethylene (11 mils) Polyester/cotton cloth Natural rubber adhesive
Material Thickness		11 mil
Adhesive Strength: to stainless steel to concrete	ASTM D1004	47 oz per inch (5.14 N/cm) 39 oz per inch (4.27 N/cm)
Tensile Strength:	ASTM D1004	27 lbs per in (47.3 N)
VOCs		Low
Installation Temperatures	ASTM D746	30°F to 200°F (-1°C to 90°C)

Pasco Construction Solutions Pty Ltd offers its' products for sale, subject to its standard terms and conditions of sale, which are available upon request. All endeavors have been made to ensure the information provided in this technical data sheet is accurate and correct, however as the use of this material is beyond the supplier's control, liability is limited to replacement of material proven faulty. It is the responsibility of the purchaser to ensure that the product is suitable for the specific application and that it is applied in accordance with the supplier's recommendations.