



## Technical Data Sheet

### U-TABS-SPIKE 4,5mm Spacer tabs

#### COMPONENTS

The U-TABS-SPIKE 4,5 mm is composed of 1 piece.

#### CHARACTERISTICS

Weight: 0,18 kg

Height: 17 mm

Height of the spike: 50 mm

#### MATERIAL

Copolymer polypropylene (CPP)

Composition: +/- 80% first grade pre-selected recycled PPC, and +/- 20% Talc + Masterbatch black

Designed and manufactured in Europe.

Use of recycled materials exclusively of EU origin.

Resistant to weathering, sea salts, algae and a wide range of chemicals.

Temperature range: -30 °C to +80 °C

#### PACKAGING

Pieces per carton: 120 pcs

Carton weight: 2,66 kg

Carton dimension: 400 x 300 x 225 mm

Cartons per pallet: 90 pcs

Pieces per pallet: 10800 pcs

Pallet dimensions: 100 x 120 x 220 cm

#### APPLICATIONS

The U-TABS SPIKE enables the direct laying of pavers on soft ground, gravel, lawn, etc. It is planted directly in the ground and facilitates the creation of terraces or Japanese steps.

#### SAFETY INSTRUCTIONS

Buzon pedestals and accessories are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.

