

Technical Data Sheet

- Primer / Sealer
- Solvent Based
- Excellent Adhesion
- Fast Curing
- No thinning required

Pasco Construction Solutions
13 – 15 Brighton Street
Richmond Vic 3121
Ph: 03 9429 9111
Fax: 03 9429 6111
www.pasco.net.au

Aquaprime SB

Solvent Based Primer For Acrylic Membranes

Description

Aquaprime SB Primer is a one part acrylic primer used to prime and seal concrete substrates. It cures to form a water resistant coating having excellent adhesion to sound concrete, plywood etc. **Aquaprime SB Primer** is an excellent primer for acrylic membrane where the substrate surface is in poor condition i.e. chalky, powdery etc.

Features/Benefits

- Primer for water-based membranes
- Excellent adhesion
- Penetrating primer
- Fast curing
- Easy to apply

Uses

- Primer for water based membranes
- Sealing of concrete floors.

APPLICATION INSTRUCTIONS

Substrate preparation

- All surfaces must be clean, sound and free from dust, oil, rust, cement droppings, protrusions, old sealant or any other contamination. Surfaces must also be free from form release and curing agents.
- Metal surfaces shall be clean and free of any rust, dirt, grease and oil. Rusted surfaces must be wire brushed or sandblasted and treated with an appropriate rust converter.

Application

1. Apply the first coat of **Aquaprime SB** to the entire area that needs to be waterproofed using a roller, brush or spray and allow to cure.
2. Apply at rate of 6-8m² per litre
3. Time between coats if required, 3 days. at 20°C

Aquaprime SB

Precautions

- Do not apply product if temperature is in excess of 35°C or less than 5°C.
- Do not apply if relative humidity is above 85%.
- Ensure product is fully cured prior to membrane application.
- Do not apply product if rain is imminent.
- Do not use under Polyurethane Membranes.

Curing

- Full Cure: 30 - 60 minutes @ 25°C
- Can be recoated after several days
- Minimum cure temperature 10°C

Coverage

Apply **Aquaprime SB** at a rate of 6 – 8m² per litre.

Clean Up

Tools and excess product can be cleaned with water while still wet. Cured material may be removed by mechanical means and the use of Pasco Xylene.

Packaging

Aquaprime SB is available in:

- 4 Litre
- 20 Litre

Colour

Aquaprime SB is available in Clear

Shelf Life

12 months minimum, when stored in cool, dry, original containers in conditions below 20°C.

Health and Safety

Keep out of reach of children. Wear suitable protective clothing, gloves and eye/face protection. Uncured product may cause skin, eye and respiratory system irritation. Use only in well ventilated areas.

In case of contact with eyes, rinse immediately with plenty of water and contact a Doctor or Poisons Information Centre (**Ph 13 11 26**). In case of skin contact, wash affected area with hand cleaner followed by soap and water.

Material Safety Data Sheets must be read and understood prior to using the product.

Pasco Construction Solutions Pty Ltd warrants its' products to be free of defects and faulty manufacture and are sold subject to its standard terms and conditions of sale, which are available upon request. All endeavors have been made to ensure the information provided in this technical data sheet is accurate and correct, however as the use of this material is beyond the supplier's control, liability is limited to replacement of material proven faulty. It is the responsibility of the purchaser to ensure that the product is suitable for the specific application and that it is applied in accordance with the suppliers recommendations.